

KEW 2007R

KEW 2007R - Kyoritsu AC Digital Clamp Meter

Rating: Not Rated Yet

2-3 Days

★★★★

[Ask a question about this product](#)

Manufacturer [KYORITSU](#)

Description

- Fully Safety jaw
- Ergonomic over-molded body gives convenient one-hand operation
- Large easy-to-read display with 0.1A resolution
- Accurate reading with True RMS
600/1000A auto-ranging
- Long battery life
- Safety Standard

IEC 61010-1 CAT IV 300V / CAT III 600V

AC A	600.0/1000A (Auto-ranging) ±1.5%rdg±4dgt [45 - 65Hz] ±2.0%rdg±4dgt [40 - 400Hz]
AC V	600.0V ±1.2%rdg±3dgt [45 - 65Hz] ±1.5%rdg±4dgt [40 - 400Hz]
DC V	600.0V ±1.2%rdg±3dgt
?	600.0?/6.000k? (Auto-ranging) ±1.3%rdg±5dgt (600?) ±2.0%rdg±3dgt (6.000k?)
Continuity buzzer	600? (Buzzer sounds below 90?)
Conductor size	?33mm max.
Applicable standards	IEC 61010-1 CAT IV 300V, CAT III 600V Pollution degree 2 IEC 61010-031, IEC 61010-2-032, IEC 61010-2-033, IEC 61326-2-2(EMC), IEC 60529 IP40, EN 50581(RoHS)
Power source	R03/LR03 (AAA) (1.5V) × 2
Continuous measuring time	Approx.170 hours (when R03 is used) (Auto power save : approx. 10 minutes)
Dimensions	204(L) × 81(W) × 36(D)mm

Clampmeter: KEW 2007R

Weight	220g Approx. (including batteries)
Included Accessories	7066A (Test leads) 9079 (Carrying case) R03 (AAA) × 2, Instruction Manual