

## KEW 2500 - DC Miliamp Clampmeter

DC Miliamp Clampmeter

Rating: Not Rated Yet  
[Ask a question about this product](#)

Manufacturer [KYORITSU](#)

Description

- 0.01mA resolution for DC current
- Top class measurement 0.2% accuracy
- Ø6mm clamp jaw easy to use in tight places
- Measurement from 0.01mA to 120.0mA
- Dual display with backlight shows both mA measurement and percent of 4-20 mA span
- Spotlight for illuminating measurement point
- Analog output terminal for recorder connection

### Specification:

|  |   |
|--|---|
| DC A                                   | 20/100mA (Auto ranging)<br>±0.2%rdg±5dgt (0.00mA - 21.49mA)<br>±1.0%rdg±5dgt (21.0mA - 120.0mA)       |
| Conductor size                         | Ø6mm max.   |
| Analog output                          | Recorder: DC 1000mV against DC 100mA  |
| Applicable standards                   | IEC 61010-1, Pollution degree 2<br>IEC 61010-2-032, IEC 61326-1(EMC)<br>IEC 60529 IP40, EN50581(RoHS) |
| Operating temperature & humidity range | -10 - +50°C < 85%   |
| Storage temperature & humidity range   | -20 - +60°C < 85%   |
| Power source                           | R6/LR6 (AA) (1.5V) × 4  |
| Dimensions                             | 111(L) × 61(W) × 40(D)mm : Display unit<br>104(L) × 34(W) × 20(D)mm : Sensor<br>700mm : Sensor cable  |
| Weight                                 | Approx. 290g (including batteries)  |
| Included Accessories                   | 9096 (Carrying case), LR6 (AA) × 4,<br>Instruction Manual   |
| Optional Accessories                   | 7256 (Output cord)  |