

## KEW 2510 - DC Miliamp Clamp Meter

DC Miliamp Clamp Meter (Bluetooth function) 20/120mA

Rating: Not Rated Yet

[Ask a question about this product](#)

Manufacturer [KYORITSU](#)

### Description



- Measures 4 to 20 mA instrumentation and process signals without breaking the loop
- Memory function stores up to 192000 data useful for monitoring the signals over time and fault finding
- Transfer data to PC via Bluetooth
- Top class measurement 0.2% accuracy
- 6mm clamp jaw easy to use in tight places
- LED light for illuminating the measurement spot
- Analog output terminal to allow the connection to a recorder or a digital multimeter

## Specification

|                |  |
|----------------|--|
| AC A           | 20/100mA(Auto ranging)<br>±0.2%rdg±5dgt (0.00mA - 21.49mA)<br>±1.0%rdg±5dgt (21.0mA - 120.0mA) |
| Conductor size | 6mm max.   |
| Analog output  | Recorder: DC1000mV against DC100mA   |

## Clampmeter: KEW 2510 - DC Milliamp Clamp Meter

|  |  |
|--|--|
| Applicable standards                   | IEC 61010-1, Pollution degree 2<br>IEC 61010-2-032, IEC 61326-1(EMC)<br>IEC 60529 IP40, EN50581(RoHS)                                  |
| Operating temperature & humidity range | -10 - +50? <85%  |
| Storage temperature & humidity range   | -20 - +60? <85%  |
| Power source                           | R6/LR6(AA) (1.5V) x4 (Alkaline LR6 is recommended.)<br>External supply (AC adapter MODEL8320)  |
| Communication interface                | Bluetooth Ver2.1+EDR Class2  |
| Dimensions / Weight                    | 111(L)x61(W)x46(D)mm : Display unit<br>104(L)x33(W)x20(D)mm : Sensor<br>700mm : Sensor Cable<br>Approx. 310g(including batteries)      |
| Included Accessories                   | 8320(AC adapter), KEW Windows for 2510(Software)<br>9096(Carrying case), LR6(AA)x4, Instruction manual<br>Software installation manual |
| Optional Accessories                   | 7256(Output cord)  |